

## SGR-8106-SPB SGR-8206-SPB

One/Two-Line  
Cordless  
Extension VoIP  
Speakerphone



### Features

- Color LCD Display
- Lithium-Ion Battery
- Hearing Aid Compatible
- Full Duplex Speakerphone
- Auto Handset/Base pairing
- Enhanced Cordless Technology
- 6 Guest Service Keys on Handset
- Charging Indicator on Charger Base
- Low Battery/out of Range Indicator
- Room Number Displayed on Handset
- Backlit DTMF, Function and Speed Dial Keys
- Message Waiting & Ringer Indicator on Handset
- Customizable Hotel Logo on Handset Display
- Adjustable Receiver and Speakerphone Volume

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## SPECIFICATIONS

Power	<ul style="list-style-type: none"> <li>• Adapter 100-240 VAC Output 6V/1A (Optional)</li> </ul>
H/S Battery	<ul style="list-style-type: none"> <li>• 3.7V / 900 mAH Li-ion Battery</li> <li>• Standby Time: 240 Hours • Talk Time: 9 Hours</li> </ul>
Weight	<ul style="list-style-type: none"> <li>• 304g</li> </ul>
RF Standard	<ul style="list-style-type: none"> <li>• DECT / CAT iq1.0 compatible</li> <li>• Radio Frequency Range: 1880-1930 Mhz</li> <li>• EU band: 1881.792(ch0)-1897.334(ch9) 10 Channels</li> <li>• US band: 1921.536(ch0)-1928.448(ch4) 5 Channels</li> <li>• Modulation GFSK                      • Power Tx: 100mW</li> </ul>
Range	<ul style="list-style-type: none"> <li>• 984 feet Outdoor                      • 164 feet Indoor (DOM)</li> </ul>
EMI	USA: FCC Part 15B,D ICES-003    EU: EN 55022
EMC	EU: EN 55024, EN 61000-4-4, EN 61000-3-2, IEC 61000-4-5 EN 61000-3-3, IEC 61000-4-6, EN 61000-4-2, IEC 61000-4-11
RoHS	<ul style="list-style-type: none"> <li>• Comply with directive 2002/95/EC RoHS (2005/613/EC)</li> </ul>
Temperature	<ul style="list-style-type: none"> <li>• Storage -10C to +60C              • Operating 0C to +45C</li> </ul>

